



**Note:**  
 KEYSTONE SHOWN CAN BE USED IN CONJUNCTION WITH ALL STANDARD HEAD TYPES

WHERE A PROJECTING KEYSTONE IS REQUIRED (KEYSTONE TYPES 1&2) THE HEAD WILL BE SUPPLIED IN MINIMUM OF 3PCS

LINTELS COMPRISING OF KEYSTONE TYPE 3&4 CAN BE SUPPLIED IN 1PC SUBJECT TO REQUIREMENTS & LENGTH RESTRICTIONS

ALL HEADS ARE NON-LOAD BEARING COMPONENTS AND MUST BE USED IN CONJUNCTION WITH A SUITABLE LOAD RELIEVING LINTEL. PLEASE CONSULT YOUR ENGINEER PRIOR TO INSTALLATION.

NON-STANDARD KEYSTONES MANUFACTURED TO ORDER  
 KEYSTONES TO SUIT LINTELS IN RENDER ALSO AVAILABLE

KEYSTONE TYPE 1&2 TO BE USED ONLY WITH LINTELS 215mm OR 290mm HIGH.  
 THE FORMER ACHIEVING A PROJECTED KEYSTONE AS ILLUSTRATED.

KEYSTONES TYPE 3&4 TO BE USED ONLY WITH LINTELS 140mm OR 215mm HIGH.  
 THE LATTER ACHIEVING FLUSH KEYSTONE AS ILLUSTRATED.

Designed by RR	Checked by	Approved by	Date	Date 24/04/2021	
PROCTER CAST STONE			Keystone 1		Edition
					Sheet 1 / 1