



Note:

KEYSTONE SHOWN CAN BE USED IN CONJUNCTION WITH ALL STANDARD HEAD TYPES

WHERE A PROJECTING KEYSTONE IS REQUIRED (KEYSTONE TYPES 1&2) THE HEAD WILL BE SUPPLIED IN MINIMUM OF 3PCS

LINTELS COMPRISING OF KEYSTONE TYPE 3&4 CAN BE SUPPLIED IN 1PC SUBJECT TO REQUIREMENTS & LENGTH RESTRICTIONS

ALL HEADS ARE NON-LOAD BEARING COMPONENTS AND MUST BE USED IN CONJUNCTION WITH A SUITABLE LOAD RELIEVING LINTEL. PLEASE CONSULT YOUR ENGINEER PRIOR TO INSTALLATION.

NON-STANDARD KEYSTONES MANUFACTURED TO ORDER
KEYSTONES TO SUIT LINTELS IN RENDER ALSO AVAILABLE

KEYSTONE TYPE 1&2 TO BE USED ONLY WITH LINTELS 215mm OR 290mm HIGH.
THE FORMER ACHIEVING A PROJECTED KEYSTONE AS ILLUSTRATED.

KEYSTONES TYPE 3&4 TO BE USED ONLY WITH LINTELS 140mm OR 215mm HIGH.
THE LATTER ACHIEVING FLUSH KEYSTONE AS ILLUSTRATED.

| | | | | | |
|-----------------------|------------|-------------|------------|--------------------|----------------|
| Designed by RR | Checked by | Approved by | Date | Date 24/04/2021 | |
| PROCTER CAST STONE | | | Keystone 3 | | Sheet 1 / 1 |
| | | | Edition | | |